



TERRY FAST FIT SERIES

TFF-CP10

Single-cartridge carbon system with scale inhibitor

A compact, wall-mounted single-cartridge system for ice, steam, cold and hot beverage. High-grade activated carbon reduces chlorine taste, odour and corrosion, while an added scale inhibitor protects downstream equipment.

6.3 L/min
SERVICE FLOW

1 μ m
SEDIMENT

8.6 bar
MAX PRESSURE



TFF-CP10 with head, shut-off valve & gauge

FEATURES

- High-grade activated carbon — reduces taste, chlorine odour & corrosion
- Inhibits hard-water scale
- Reduces costly equipment maintenance
- Full-port shut-off valve
- In-line pressure gauge

CERTIFICATION

- NSF/ANSI 42 — aesthetic effects (Systems IV FF-CP10)
- NSF/ANSI 53 — health effects (Systems IV FF-CP10)

TERRY FAST FIT SERIES

Specification

TFF-CP10 · P/N 57511001

Product dimensions	432 × 203 × 114 mm
Connection	3/8" FNPT
Max. pressure	8.6 bar (125 psi)
Max. temperature	38 °C
Service flow rate	6.3 L/min
Sediment reduction	1 micron
Product weight	0.7 kg

APPLICATIONS

- Ice — cubers ≤ 360 kg, flakers ≤ 545 kg
- Steam — single-compartment & countertop
- Cold beverage — 1 carbonator, 1–8 dispensers
- Hot beverage

REPLACEMENT & NOTES

- Replace cartridge every 6 months or on pressure drop
- Commercial use only
- Install per manufacturer guidelines

Specifications are nominal and subject to change without notice. Imperial source data converted to metric.