



TERRY FAST FIT SERIES

TFF-C10SYS

Single-cartridge carbon system · cold & hot beverage

A single-unit water treatment system that reduces sediment, chlorine, taste and odour with an advanced carbon-block filter to 0.5 micron, while reducing scale-related problems. Fast-Fit cartridge for quick change-out.

6.3 L/min
SERVICE FLOW

0.5 µm
SEDIMENT

8.6 bar
MAX PRESSURE



TFF-C10SYS with head, valve & gauge

FEATURES

- High-grade activated carbon — reduces taste, chlorine odour & corrosion
- Fast-Fit quick-change cartridge
- Inhibits hard-water scale
- Reduces costly equipment maintenance
- Full-port shut-off valve
- In-line pressure gauge

CERTIFICATION

- NSF/ANSI 42 — aesthetic effects (Systems IV FF-C10)
- NSF/ANSI 53 — health effects (Systems IV FF-C10)

TERRY FAST FIT SERIES

Specification

TFF-C10SYS · P/N 57511002

Product dimensions	432 × 203 × 114 mm
Connection	3/8" NPT
Capacity	45,400 L (12,000 gal)
Max. pressure	8.6 bar (125 psi)
Max. temperature	38 °C
Service flow rate	6.3 L/min
Sediment reduction	0.5 micron
Shipping weight	1.6 kg
Replacement cartridge	TFF-C10R · P/N 57560002

APPLICATIONS

- Cold & hot beverage
- Carbonators up to 6.3 L/min

REPLACEMENT & NOTES

- Replace every 6 months or on pressure drop
- Filter life depends on water quality
- Commercial use only

Specifications are nominal and subject to change without notice. Imperial source data converted to metric.