



TERRY RO SERIES

Terry H2O RO 650 / RO 1200

High-demand RO with 15" filters & dual-membrane option

Built for higher-demand sites, the RO 650 series uses larger 15" filters for extended life, greater flow and increased capacity. The RO 1200 runs a dual-membrane configuration up to 4,540 L/day, plus a carbon and remineralisation post-filter for optimal flavour and mineral balance.

2,460 L/day
RO 650 (UP TO)

4,540 L/day
RO 1200 (UP TO)

15"
EXTENDED-LIFE FILTERS



Terry H2O RO 650

FEATURES

- 15" filters for extended life & higher flow
- Stainless enclosure, tool-free access
- Three pressure gauges (feed, pump, tank)
- Integrated TDS monitor & mineral blending
- High-efficiency permeate pump
- Manual membrane flush valve

CERTIFICATION

- Line-pressure or booster-pump operation

TERRY RO SERIES

Specification

Terry H2O RO 650 / RO 1200 · incl. booster-pump variant

RO 650 permeate	2,460 L/day (650 GPD)
RO 1200 permeate	4,540 L/day (1,200 GPD)
RO 1200 membranes	Dual, + carbon/remin post-filter
Filters	15" extended-life
Models	RO 650 · RO 650 booster · RO 1200
Enclosure	Stainless steel, tool-free access
Gauges	Feed, pump & tank

APPLICATIONS

- High-volume cafés
- Food-service operations
- Commercial environments

REPLACEMENT & NOTES

- RO 650 — standard line pressure
- RO 650 booster — low/fluctuating pressure
- RO 1200 — dual-membrane high output

Specifications are nominal and subject to change without notice. Imperial source data converted to metric.