

COLD BEVERAGE · TERRY

TFF-C10SYS

Single 10" carbon system for taste and odour control with 1 micron particulate filtration.

6.3 l/min
SERVICE FLOW**8.6 bar**
MAX PRESSURE**6 months**
CARTRIDGE LIFE

SPECIFICATION

Flow rate	6.3 l/min (1.67 GPM)
Filtration	1 micron particulate
Media	High-grade activated carbon — taste & odour
Application	1 carbonator, drinking fountain, 1–2 brewers
Cartridge life	up to 6 months
Operating pressure	1.7 – 8.6 bar (25 – 125 psi)
Operating temperature	1.7 – 38 °C (35 – 100 °F)
Mounting	Wall-mounted stainless steel bracket
Power supply	None required — line-pressure operation
Certification	NSF/ANSI 42 — tested and certified

REGIONAL WATER CONTEXT · GULF HARD WATER

300–600 mg/L as CaCO₃ **VERY HARD**

30–60 °f · 17–34 °dH · 18–35 gpg

Gulf feed water varies by source: desalinated municipal supply is soft, but groundwater, blended and tank-stored supplies commonly run hard to very hard. Ice, steam and warewash equipment then concentrate that hardness several-fold at the point of use — which is where scale forms fastest.

Specifications are nominal and subject to change without notice. Imperial figures converted from metric source data.