

TWO-STAGE · TERRY

TPS-C10S15

Two-stage system: chlorine, taste and particulate on stage one, CITRYNE® scale elimination on stage two.

7.6 l/min

SERVICE FLOW

8.6 bar

MAX PRESSURE

6 months

CARTRIDGE LIFE



SPECIFICATION

Stage 1	10" × 4" carbon — reduces chlorine, taste, odour and particulates
Stage 2	15" × 4" CITRYNE® — scale elimination and prevention
Flow rate	7.6 l/min (2 GPM) maximum service flow
Operating pressure	1.7–8.6 bar (25–125 psi)
Operating temperature	1.7–38 °C (35–100 °F)
Certification	NSF/ANSI 42 — cyst reduction
Cartridge life	up to 6 months, both stages
Part numbers	System 58022002 · replacement packs 58052002
Operating pressure	1.7 – 8.6 bar (25 – 125 psi)
Operating temperature	1.7 – 38 °C (35 – 100 °F)
Mounting	Wall-mounted stainless steel bracket
Power supply	None required — line-pressure operation
Certification	NSF/ANSI 42 — tested and certified

REGIONAL WATER CONTEXT · GULF HARD WATER

300–600 mg/L as CaCO₃ **VERY HARD**

30–60 °f · 17–34 °dH · 18–35 gpg

Gulf feed water varies by source: desalinated municipal supply is soft, but groundwater, blended and tank-stored supplies commonly run hard to very hard. Ice, steam and warewash equipment then concentrate that hardness several-fold at the point of use — which is where scale forms fastest.

